

B105 - 20F



B105 - 20B



NOTES


- 1. BURR OF BRACKET SHOULD BE MINIMIZED.
- 2. BRACKET SHOULD BE FREE OF SHARP EDGES.
- 3. UNSPECIFIED RADIUS WOULD BE 0.5MM.
- 4. IMPORTANT PARTS ARE MARKED BY ASTERISK.
- 5. SAMPLE APPROVAL IS REQUIRED.


GENERAL TOLERANCES (mm)


| | 521121012 1 52210111525 (mm) | | | |
|---------|------------------------------|----|----------|--|
| 0 | ~ | 10 | +/- 0.20 | |
| 11 | ~ | 25 | +/- 0.25 | |
| 26 | ~ | 38 | +/- 0.30 | |
| 39 | ~ | 50 | +/- 0.40 | |
| OVER 50 | | 50 | +/- 0.50 | |

| ITEM NO. | B105 - 20 |
|-------------|-----------------------|
| DESCRIPTION | RANGER BELT |
| MATERIAL | ALU6061 - T6, T = 8MM |
| WEIGHT | 15.36g |
| DATE | 01/AUG/2024 |









B105 - 25F



B105 - 25B



NOTES


- 1. BURR OF BRACKET SHOULD BE MINIMIZED.
- 2. BRACKET SHOULD BE FREE OF SHARP EDGES.
- 3. UNSPECIFIED RADIUS WOULD BE 0.5MM.
- 4. IMPORTANT PARTS ARE MARKED BY ASTERISK.
- 5. SAMPLE APPROVAL IS REQUIRED.


GENERAL TOLERANCES (mm)


| | | | - () |
|---------|---|----|----------|
| 0 | ~ | 10 | +/- 0.20 |
| 11 | ~ | 25 | +/- 0.25 |
| 26 | ~ | 38 | +/- 0.30 |
| 39 | ~ | 50 | +/- 0.40 |
| OVER 50 | | 50 | +/- 0.50 |

| ITEM NO. | B105 - 25 |
|-------------|-----------------------|
| DESCRIPTION | RANGER BELT |
| MATERIAL | ALU6061 - T6, T = 8MM |
| WEIGHT | 23.60g |
| DATE | 01/AUG/2024 |









B105 - 32F



B105 - 32B



NOTES


- 1. BURR OF BRACKET SHOULD BE MINIMIZED.
- 2. BRACKET SHOULD BE FREE OF SHARP EDGES.
- 3. UNSPECIFIED RADIUS WOULD BE 0.5MM.
- 4. IMPORTANT PARTS ARE MARKED BY ASTERISK.
- 5. SAMPLE APPROVAL IS REQUIRED.


GENERAL TOLERANCES (mm)


| | | | - () |
|----|---------|----|----------|
| 0 | ~ | 10 | +/- 0.20 |
| 11 | ~ | 25 | +/- 0.25 |
| 26 | ~ | 38 | +/- 0.30 |
| 39 | ~ | 50 | +/- 0.40 |
| 0 | OVER 50 | | +/- 0.50 |

| ITEM NO. | B105 - 32 |
|-------------|-----------------------|
| DESCRIPTION | RANGER BELT |
| MATERIAL | ALU6061 - T6, T = 8MM |
| WEIGHT | 27.60g |
| DATE | 01/AUG/2024 |









B105 - 38F



B105 - 38B



NOTES

- 1. BURR OF BRACKET SHOULD BE MINIMIZED.
- 2. BRACKET SHOULD BE FREE OF SHARP EDGES.
- 3. UNSPECIFIED RADIUS WOULD BE 0.5MM.
- 4. IMPORTANT PARTS ARE MARKED BY ASTERISK.
- 5. SAMPLE APPROVAL IS REQUIRED.

GENERAL TOLERANCES (mm)

| , (······, | | | |
|------------|---|----|----------|
| 0 | ~ | 10 | +/- 0.20 |
| 11 | ~ | 25 | +/- 0.25 |
| 26 | ~ | 38 | +/- 0.30 |
| 39 | ~ | 50 | +/- 0.40 |
| OVER 50 | | 50 | +/- 0.50 |

| ITEM NO. | B105 - 38 |
|-------------|-----------------------|
| DESCRIPTION | RANGER BELT |
| MATERIAL | ALU6061 - T6, T = 8MM |
| WEIGHT | 34.10g |
| DATE | 01/AUG/2024 |